

MARIGOLD 3600 BHP Anchor handling Tug

SHIP PARTICULAR

CLASSIFICATION

AHT Type Year Built July 2009 Owner / Operator Triton Maritime Pvt. Ltd. Flag Indian Port of Registry Mumbai **IMO** Number 9555541 **Classification Society** IRS

PRINCIPAL DIMENSION

LOA Breadth Depth Draft Deadweight GRT / NRT

11.40 mtr 4.95 mtr 4.00 mtr 350 t 475 / 143

37.00 mtr

PROPULSION Main Engine

Generator

Propeller

Bow Thruster

2 Nos. (Cummins KTA50m-2; BHP 2 x 1800 BHP = 3600 BHP 2 Nos. (Cummins 2 X 6 BT5.9D; 2 x 97 kW) Kamome 3.0 t Drive by Cummins 2.2 M Fixed Pitch 4.65 M with Kort Nozzles

AHT EQUIPMENT

AHT Winch

Make & Type	Ν
Tow Wire	5
Spare Tow Wire	5
Anchor Handling Wire	2
Tugger Winch	1
Vertical Capstan	1

Brake Holding Cap. 150t, Bollard Pull 45 t, 32 mm Wire Marine Equipment Pvt. Ltd. 50 mm dia x 750 m 50 mm dia x 750 m x 32 mm dia L – 200 M x 5T x 5T

SAFETY EQUIPMENTS

LSA	Standard SOLAS equipment as
	applicable to vessel
FFA	Standard SOLAS equipment as
	applicable to vessel
Rescue Boat	Fire Retardant FRP davit launched
Capacity	6 persons, max speed 6.16 kts
	with full load
CAPACITIES	
Fresh Water	59 m3

Fresh Water	59 m3
Ballast water	Nil
Fuel	220 MT
Accommodation	18
Clear Deck Area	100 m2

SPEED

12.5 Kts
7.5 Kts
9 KL of MGO / Day @ Full MCR
6 KL of MGO / Day @ Eco Speed

MOORING AND ANCHOR WINDLASS DETAILS

Capacity	3 T
Make / Model	Marine Equipment Pvt. Ltd.
Anchors	2 Stockless bower

NAVIGATIONAL AND COMMUNICATIONS EUIPMENTS

GMDSS Area A1 + A2 + A3 Navigational Equipment Unrestricted navigation (No ECIDS)





MARIGOLD

